

Product Information


Mod.R&S 06 | Rev.4 | Update 10/2017 | Page 1



P.S. STRETCH

Description

PU plotter cut heat seal material with adhesive polyester backing. The material is thin, elastic, soft to the hand and blends well into the textiles, granting also an easy weeding and application. Specifically designed for textiles featuring elastic qualities. Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex, not treated or dye sublimated



Ū

Suggested cutting settings

blade new at 45° pressure 50 gf speed 20 cm/sec

Transfer settings

15 seconds at 155°C medium pressure (3-4 bar)


Usage

- Mirror cut the material
- Weed the exceeding material
- Place the material on the garment with its polyester backing
- Heat apply at the conditions shown on the right
- Remove the support warm or cold

Washing

Wait at least **24 hours** from application before washing. Washing resistance up to **60°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning Suitable for tumble dry, cotton cycle

The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class I





Dry cleaning



Tumble dryer





N.B. All information here contained are based on our experience.
 We recommend to perform a test before starting standard production.
 For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



Management System ISO 9001:2015

www.tuv.com



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance). This document can be subject to variations. Updated versions are available on our website www.siser.com For further information, please contact our Sales Office. Thank you

