

SYNAPS OM in a nutshell:

SYNAPS OM is a white opaque high grade polyester based synthetic print media with a matt finish. Water and tear resistant, SYNAPS OM offers a most cost efficient alternative to laminating paper print with foil. SYNAPS OM is unique in the synthetic print media market in offering incomparable printability with standard offset inks. As such, it offers a true drop-in solution for offset printers for the production of print materials with particularly demanding user environment. Its antistatic properties and dimensional stability allow for flawless printing and finishing, and thanks to its exceptionally fast drying quality SYNAPS OM is extremely suitable for quick 'print and turn' jobs. The growing range of applications includes indoor and outdoor POS signage, menu cards, tab sheets, labels and tags, just to name a few.

For recommendations for printing and finishing, please consult the SYNAPS OM 'Technical Documentation' section on www.agfa.com/synaps/dedicated web page

Technical Data
SYNAPS OM
Offset matt

version 1.1 - 2013-10-25

Property	Test method	Unit	OM 135	OM170	OM230	OM300	OM450
Thickness Average	ASTM D-6988	µm	120 ± 7	150 ± 8	200 ± 10	250 ± 12	350 ± 21
Weight		g/m ²	135	170	230	300	450
Shrinkage	Internal Agfa test at 95°C/203°F	%	≤0,2	≤0,2	≤0,2	≤0,2	≤0,2
Brittleness	Internal Agfa test	°C (°F)	≤-40 (≤-40)	≤-40 (≤-40)	≤-40 (≤-40)	≤-40 (≤-40)	≤-40 (≤-40)
Initial tear strength	ASTM D1004	N	≥45	≥55	≥80	≥100	≥125
Stiffness	ISO 2493	mN	≥5	≥10	≥25	≥48	≥110
BEKK smoothness	ISO 5627	Sec	500-1000	500-1000	500-1000	500-1000	500-1000
Opacity	ISO 2471	%	≥92	≥94	≥96	≥96	≥97
Brightness	ISO 2470C		≥95	≥95	≥95	≥95	≥93
Whiteness Cie	ISO 11475		≥100	≥100	≥100	≥98	≥95
Gloss 75°	Tappi T480		3-5	3-5	3-5	3-5	3-5
Mass density	ISO 534	g/cm ³	1,13 ± 0,05	1,14 ± 0,05	1,16 ± 0,05	1,22 ± 0,05	1,26 ± 0,05
Fire Class			Information upon request	Information upon request	Information upon request	Information upon request	Information upon request