



SELF-ADHESIVE ONE WAY VISION FILM

Power View is a perforated, self-adhesive window film especially designed for short term applications. Power View is made of calendared vinyl, equipped with clear semi-permanent adhesive.

# **APPLICATIONS**

- building wraps
- shop windows
- all applications up to 6 months

## **ADVANTAGES**

- designed to be comined with the over laminate panoRama Cast or Protect for flat surfaces.
- printable with solvent, eco-solvent, UV curable inks and latex
- 6 months durability warranty if applied under mid European conditions
- removability up to 6 months under normal conditions
- calendered vinyl features great dimensional stability
- special liner finish enables an easy handling when applying on the window
- semi-permanent, clear adhesive offers good removability



www.continentalgrafix.com info@continentalgrafix.com



# Power View

SELE-ADHESIVE ONE WAY VISION FILM

#### MATERIAI

- perforated vinyl film
  - 145 micron
  - self adhesive
  - printable white front side
- black reverse side for maximum contrast
- excellent dimensional stability
- removable, semi-permanent clear adhesive

## LINER

special liner finish

<sup>-</sup> - 150 g/m2

# OPEN AREA / PRINTABLE AREA

• open area: 40%

• printable area: 60%

## PRINTING METHOD

- digital
  - solvent, eco-solvent
- UV curable inks
- latex

HUMIDITY AND SOLVENT RESISTANCE good

MIN. APPLICATION TEMPERATURE +10°C to +30°C (+50°F to +86°F)

SERVICE RANGE TEMPERATURE -17°C to +50°C (+0°F to +122°F)

### SHFL FLIFF

1 year, stored at +15 to  $+20^{\circ}$  C (+59 to  $+68^{\circ}$  F) and relative humidity between 45% and 65%.

#### DURABILITY

Up to 6 months in mid European conditions. Clean removal within 6 months. Tack may increase over time. Not to be applied on: fresh paint or ink, polycarbonate, certain PVC (no exhaustive list). For critical substrates, please test prior to application.

## APPLICATION

Prevent from contact with solvent or ammonia based cleaner. Clean window with soap and water. Rinse and dry glass after cleaning. ALWAYS clean and dry glass prior to application. Please respect our application instructions.



